

2.11 PROTECTIVE TRIM UNITS, GENERAL

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that maybe incorporated into the Work include, but are not limited to, the following:
- B. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - 1. Metal Protective Trim Units:
 - a. Baldwin Hardware Corporation.
 - b. Hager Companies.
 - c. Hiawatha, Inc.
 - d. Ives: H. B. Ives.
 - e. Rockwood Manufacturing Company.
- C. Standard: Comply with BHMA A156.6.
- D. Materials: Fabricate protection plates from the following:
 - 1. Stainless Steel: 0.050 inch (1.3 mm) thick; beveled top and two sides.
- E. Fasteners: Provide manufacturer's standard exposed fasteners for door trim units consisting of either machine or self-tapping screws.
- F. Furnish protection plates sized 1-1/2 inches (38 mm) less than door width on push side and 1/2 inch (13 mm) less than door width on pull side, by height specified in schedule.

2.12 PROTECTIVE TRIM UNITS

- A. Armor Plates: 36 inches (914 mm) high by door width, with allowance for frame stops.
- B. Kick Plates: 12 inches (305 mm) high by door width, with allowance for frame stops.
- C. Mop Plates: 6 inches (152 mm) high by 1 inch (25 mm) less than door width.
- D. Stretcher Plates: 8 inches (203 mm) high by door width, with allowance for frame stops.
 - 1. Nonmortise Cap Door Edging: Consisting of minimum 0.050-inch- (1.3mm-) thick metal sheet)].

2.13 STOPS AND HOLDERS, GENERAL

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - 1. Baldwin Hardware Corporation.
 - 2. Hager Companies
 - 3. Ives: H. B. Ives.
 - 4. Norton Door Controls; Div. of Yale Security Inc.
 - 5. Rixson-Firemark, Inc.; Div. of Yale Security Inc.
 - 6. Rockwood Manufacturing Company.
 - 7. Yale Security Inc.; Div. of Williams Holdings.
- B. Standards: Comply with the following: